



- A SEA WATER DRAIN POINT, 2x
- B SEA WATER INLET, CONNECTION FOR 63 mm (2 1/2") I.D. HOSE
- C1 WET EXHAUST BEND WITH RISER, OPTION 1
- C2 EXHAUST FLANGE, OPTION 2, MAX LOAD 9KG
- D FLEXIBLE SUSPENSION, STANDARD EQUIPMENT
- E1 OIL DIPSTICK AND FILLING ENGINE STARBOARD SIDE ALTERNATIVE
- E2 OIL DIPSTICK AND FILLING ENGINE PORT SIDE ALTERNATIVE
- F OUTLET FOR OIL BILGE PUMP (M18x1,5)
- G FRESH WATER FILLING (EXPANSION TANK)
- H FRESH WATER DRAIN POINT (3x)
- I OIL FILTER 2x
- J BYPASS OIL FILTER
- K FUEL FILTER/ WATER SEPARATOR
- L PRIMER PUMP
- M FUEL DEAIRATION
- N CONNECTOR DIAGNOSIS
- O CONNECTOR INTERFACE - EVC
- P CONNECTOR ENGINE STOP
- Q CONNECTOR WIF 2
- R1 CONNECTION BATTERY POS.
- R2 CONNECTION BATTERY NEG.
- S AIR FILTER
- T PRESSURE DROP INDICATOR, AIR FILTER
- U LIFTING EYE, 3x (Ø30 MIN. FRONT EYE REMOVABLE)
- V HOSE CONNECTION HOT WATER OUTLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- W HOSE CONNECTION HOT WATER INLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- X FUEL CONNECTION INLET 1/4"-18 NPTF
- Y FUEL CONNECTION OUTLET 1/4"-18 NPTF
- Z PRESSURE LUBRICATION FOR PROP SHAFT (1/4"-18NPTF)
- AA SEA WATER OUTLET FOR 2 1/8" I.D. HOSE (O.D. 54mm)
- AB CONNECTOR DATALINK
- AC CONNECTOR SENSORS
- AD AUTOMATIC FUSE, 10A (ENGINE)
- AE STOP BUTTON
- AF AUTOMATIC FUSE, 10A (EVC)
- AG OIL DIPSTICK AND FILLING TRANSMISSION
- AH OIL DRAIN TRANSMISSION
- AI EMERGENCY SHIFTING
- AJ PCU
- AK AUXILIARY BUS

SCALE 1:5
NET WEIGHT 1768KG (WITH OIL AND WATER)
DRY WEIGHT 1668KG (WITH OIL AND WATER)
DIMENSIONS IN MILLIMETRE AND INCHES

ENGINE DIMENSIONS
D138-B MP
REVERSE GEAR ZF 335 1V

VOLVO PENTA

22588398 01