



- A SEA WATER DRAIN POINT, 2x
- B SEA WATER INLET, CONNECTION FOR 63 mm (2 1/2") I.D. HOSE
- C1 TIE EXHAUST BEND WITH RISER, OPTION 1
- C2 EXHAUST FLANGE, OPTION 2, MAX. LOAD 9KG
- D FLEXIBLE SUSPENSION, STANDARD EQUIPMENT
- E1 OIL DIPSTICK AND FILLING ENGINE STARBOARD SIDE ALTERNATIVE
- E2 OIL DIPSTICK AND FILLING ENGINE PORT SIDE ALTERNATIVE
- F OUTLET FOR OIL BILGE PUMP (Ø16x15)
- G FRESH WATER FILLING (EXPANSION TANK)
- H FRESH WATER DRAIN POINT (3x)
- I OIL FILTER, 2x
- J BYPASS OIL FILTER
- K FUEL FILTER/WATER SEPARATOR
- L PRIMER PUMP
- M FUEL DEARATION
- N DIAGNOSIS CONNECTION (6-POLE)
- O CONNECTION SENSORS (6-POLE)
- P DATALINK CONNECTION (6-POLE)
- Q CONNECTION EVC (REVERSE GEAR/32-POLE)
- R1 CONNECTION BATTERY POS.
- R2 CONNECTION BATTERY NEG.
- S AIR FILTER
- T PRESSURE DROP INDICATOR, AIR FILTER
- U LIFTING EYE, 3x (Ø30 MIN. FRONT EYE REMOVABLE)
- V HOSE CONNECTION HOT WATER OUTLET R/2" I.D. HOSE, OPTIONAL EQUIPMENT
- W HOSE CONNECTION HOT WATER INLET R/2" I.D. HOSE, OPTIONAL EQUIPMENT
- X FUEL CONNECTION INLET
- Y FUEL CONNECTION OUTLET
- Z PRESSURE LUBRICATION OF PROP SHAFT (1/4"-18NPS)
- AA SEA WATER OUTLET FOR 2 1/8" I.D. HOSE (O.D. 54mm)
- AB EXTERNAL STOP CONNECTION
- AC CAN2 CONNECTION
- AD AUTOMATIC FUSE, 10A (ENGINE)
- AE STOP BUTTON
- AF AUTOMATIC FUSE, 10A (EVC)
- AG OIL DIPSTICK AND FILLING TRANSMISSION
- AH OIL DRAIN TRANSMISSION
- AI EMERGENCY SHIFTING

SCALE 1:5  
 WET WEIGHT 1766KG (WITH OIL AND WATER)  
 DRY WEIGHT 1666KG (WITH OUT OIL AND WATER)  
 DIMENSIONS IN MILLIMETRE AND INCHES

<p><b>VOLVO PENTA</b></p>	
<p>ENGINE DIMENSIONS                  0108-B MP                  REVERSE GEAR MEX 5096A</p>	<p>ENGINE DIMENSIONS                  0108-B MP                  REVERSE GEAR MEX 5096A</p>
<p>DISPOSITION DRAWING                  21351705</p>	<p>DISPOSITION DRAWING                  21351705</p>