



- A SEA WATER DRAIN POINT, 2x
- B SEA WATER INLET, CONNECTION FOR 63 mm (2 1/2") I.D. HOSE
- C1 WET EXHAUST BEND WITH RISER, OPTION 1
- C2 EXHAUST FLANGE, OPTION 2, MAX LOAD 9KG
- D FLEXIBLE SUSPENSION, STANDARD EQUIPMENT
- E1 OIL DPSTICK AND FILLING ENGINE STARBOARD SIDE ALTERNATIVE
- E2 OIL DPSTICK AND FILLING ENGINE PORT SIDE ALTERNATIVE
- F OUTLET FOR OIL BILGE PUMP (M8x15)
- G FRESH WATER FILLING (EXPANSION TANK)
- H FRESH WATER DRAIN POINT (3x)
- I OIL FILTER, 2x
- J BYPASS OIL FILTER
- K FUEL FILTER/ WATER SEPARATOR
- L PRIMER PUMP
- M FUEL DEARATION
- N DIAGNOSIS CONNECTION (6-POLE)
- O CONNECTION SENDERS (6-POLE)
- P DATA LINK CONNECTION (6-POLE)
- Q CONNECTION EYE (REVERSE GEAR) 32-POLE
- R1 CONNECTION BATTERY POS.
- R2 CONNECTION BATTERY NEG.
- S AIR FILTER
- T PRESSURE DROP INDICATOR, AIR FILTER
- U LIFTING EYE, 3x (Ø30 MIN. FRONT EYE REMOVABLE)
- V HOSE CONNECTION HOT WATER OUTLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- W HOSE CONNECTION HOT WATER INLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- X FUEL CONNECTION INLET
- Y FUEL CONNECTION OUTLET
- Z PRESSURE LUBRICATION OF PROP SHAFT (1/4"-18NPSF)
- AA SEA WATER OUTLET FOR 2 1/8" I.D. HOSE (OD: 54mm)
- AB EXTERNAL STOP CONNECTION
- AC CANZ CONNECTION
- AD AUTOMATIC FUSE, 10A (ENG)
- AE STOP BUTTON
- AF AUTOMATIC FUSE, 10A (EV)
- AG OIL DPSTICK AND FILLING TRANSMISSION
- AH OIL DRAIN TRANSMISSION
- AI EMERGENCY SHIFTING

SCALE 1:5  
 WET WEIGHT 5995G (WITH OIL AND WATER)  
 DRY WEIGHT 5595G (WITH OIL AND WATER)  
 DIMENSIONS IN MILLIMETRE AND INCHES

	SPECIAL DIMENSIONS AND OTHERS DIMENSIONS REFER TO 01-02-03	ENGINE DIMENSIONS 0108-B MP REVERSE GEAR ZF 305-1AE
	ENGINE DRAWING 2135-1700	03
	2135-1700	1111
	03	1111